

Hulk Crystalliser

*No other crystalliser
looks like it, or lasts like it*

Probably the best crystalliser in the world. Hulk gives the highest shine and most durable finish available to date. There is no need to use expensive steel wool with Hulk, just a White, Red or Natural Fibre Floor Pad. Add Hulk to water and work in to the floor with any slow speed rotary floor machine (even scrubber driers), within minutes a finish is revealed that is breath taking; and uniquely, Hulk strengthens the floor beneath that wonderful finish, offering a durability that is second to none.

*Hulk Crystallising Powder –
It's incredible*

Directions for Use

After regrinding and polishing the floor area with abrasives, ensure floor is cleaned of any slurry and vacuumed away. We recommend the floor should be finished to at least 400 Grade (Diamond). For maintenance as follows:

Apply 20 grams of Hulk Powder to 1m² of floor. Use a slow speed floor rotary (200rpm max.) with a white, red or natural fibre pad. Place at least ½ ltr of water onto the floor and work product into floor for 3-5 minutes. The resulting mixture when working the floor should be a green watery solution. Do not allow product to thicken up like a cream. Do not let the mixture dry out under floor machine. After 3-5 minutes add a further 1 ltr of water, work in with rotary machine then vacuum up immediately. Give final rinse with clean fresh water.

The active ingredient within Hulk has now reacted with the calcium structure of the stone and has left a crystallised finish. This finish offers a high gloss and hardened surface easing maintenance, increasing the friction coefficient and enhancing the floor's aesthetics

To improve floor without resurfacing simply use Hulk as a maintenance or repair product as outlined above.

When using, please refer to separate CO SSH Assessment Information.



CRAWSHAW'S